

## DIPENTENE – SOLVENTE AP 50 (SUPERGRADE)

SOLVENT OBTAINED BY DISTILLATION OF PINE OIL.

**DIPENTENE – SOLVENTE AP 50 (SUPERGRADE)** IT IS WIDELY USED IN INDUSTRIAL DEGREASERS, PROVIDING HIGH CLEANING EFFICIENCY AND PERFORMANCE. IN ADDITION, IT FINDS APPLICATIONS IN THE PERFUMERY INDUSTRY, ENHANCING FRAGRANCE FORMULATIONS WITH IMPROVED STABILITY AND COMPATIBILITY. IT HAS GOOD COMPATIBILITY WITH VARIOUS ORGANIC COMPONENTS, HIGH STABILITY, AND PERFORMANCE IN INDUSTRIAL, COSMETIC, AND CHEMICAL APPLICATIONS.

### PROPERTIES

Analysis	UN	Specification	Typical Values	Method
ACID NUMBER	mg KOH/g	Max. 0.5	0.11	ML SCDV 003
WATER CONTENT	%	Max. 0.5	0.04	ML SCDV 025
DENSITY (20°C)	g/ml	0.850- 0.870	0.860	ML SCDV 013
REFRACTIVE INDEX (20°C)	-	1.460- 1.480	1.469	ML SCDV 014
APHA COLOR	-	Max. 30	10.44	ML SCDV 015
ALPHA PINENE (CG)	%	Min. 50	52	ML SCDV 026

### PACKAGING

Type	Size	Shelf life
ISOTANKS (IN BULK)	-	12 months
STEEL DRUMS	170 kg	06 months

### DISCLAIMER

To prevent accidents and environmental impacts, please check the product SDS. We request our customers to test our products before using them on industrial scale. The user of our products bears the responsibility of determining their suitability for a particular application or formulation or determining that the products or their use do not infringe any intellectual property. We do not assume any responsibility or warranty, expressed or implied, resulting from handling, usage and storage whether performed according to the instructions contained in this document, whether used alone or in combination with other products. The buyer assumes all responsibility and liability for loss or damage arising from the handling and use of our products, either alone or in combination with other products.

